


SiO₂ Fibrous Adsorbent



TECHNOLOGY

Silica fibrous material produced by centrifugal spinning is a special functional material with unique properties. It can adsorb 40 % more water than classical silicagel. In addition it can also harmful organic compounds and heavy metals.

MATERIAL CHARACTERISTICS

specific surface area	600 – 900 m ² /g
typical fiber diameter	800 – 1200 nm
fiber length	continuous*
fiber structure	amorphous
physical form	3D cotton or powder
most efficient in RH	40 – 60% RH

* Fiber can be milled down to several microns.


APPLICATIONS

Adsorbent | Catalyst carrier | Filtration
Separation | Battery electrodes | Sensors

VALUE PROPOSITION

- adsorption capacity up to **40 % of its own weight**
- **3D cotton-like structures**
- **no electrostatic charge**, easy handling
- **easy desorption at lower temperatures**
- **large industrial amounts available**,
produced by Pardam, Ltd., www.pardam.cz
- **spun solution:**
 - o without any chlorine agents
 - o without toxic elements
 - o without surfactants


H₂O adsorption 25 °C, different RH



SiO₂ physical form cotton & powder



Centrifugal Spinning Technology



INVENTORS

Dr. Jan Macak
Ludek Hromadko
prof. Roman Bulanek
Eva Koudelkova

Pardam Ltd.:
Jan Buk
Miroslav Tejkl, Ph.D.

PATENT SITUATION

Czech patent granted
CZ306370B6.

CONTACT PERSON

Karolina Kasparova
karolina.kasparova@upce.cz

Commercialization Manager
Centre for Technology and
Knowledge Transfer